



89.00 EUR
incl. 19% VAT, plus [shipping](#)

- INTEL® H61 Express Chipset
 - Support 2nd generation Intel Core processor(i3/i5/i7) family
 - Multi-monitor support with Windows * 7
 - Support PCI-Express 2.0
 - Support USB 3.0
 - Support Dual Channel DDR3 1333/1066
 - Integrated HD Audio CODEC with 6.0 CH
 - Support Gigabit LAN
 - 3+1+1 Phase CPU Power Support
 - Ready for Windows® 7™
 - ITX Form Factor(170mm X 170mm)
- **CPU**
 - **INTEL® LGA1155 Socket**
 - Support 2nd generation Intel Core processor(i3/i5/i7) family
 - Support Intel® Pentium® processor, and Intel® Celeron® processor.
 - Support Intel® Turbo Boost Technology 2.0
 - 3+1+1 Phase CPU Power Support
 - **Chipset**
 - INTEL® H61 Express Chipset
 - Dual Channel DDR3 memory technology
 - **Memory**
 - 2 x DDR3 DIMM slots
 - Support DDR3 1333/1066 un-buffered memory
 - Max. capacity of system memory up to: 8GB
 - **Expansion Slots**
 - 1x PCI Express 2.0 x16(By 16) slot
 - **Storage**
 - **Embedded INTEL H61 Chipset:**
 - 4 x Serial ATA2 3Gb/s connectors
 - VIA VT1705 Audio CODEC
 - **Audio**
 - 5.1 CH HD Audio with Content Protection
 - RTL8111E Chip
 - **Ethernet LAN**
 - PCI-Ex1 Gigabit LAN 10/100/1000 Mb/s
 - Support PXE
 - **USB**
 - **INTEL H61 Chipset:**
 - 6 x USB 2.0 ports (4 distribute in back panel, 2 distribute in mid-board)
 - 2 x USB 3.0 ports by ASMedia ASM1042 (2 distribute in back panel)

-
- **Back Panel I / O**
 - 4 x USB 2.0/1.1 ports
 - 2 x USB 3.0 ports
 - 1 x PS/2 Keyboard / Mouse
 - 1 x VGA Port
 - 1 x DVI-D Port
 - 1 x HDMI Port
 - 1 x RJ-45 Port
 - 3 x Audio jacks (Line In/Line Out/Microphone)
 - 1 x USB 2.0/1.1 header for 2 USB 2.0/1.1 ports
 - CPU / Chassis Fan connectors
 - **Internal I / O**
 - 1 x 4-pin ATX 12V Power connector
 - 1 x 24-pin ATX Power connector
 - 1 x HDMI_SPDIF header
 - 1 x Front panel audio header
 - **BIOS**
 - 32 MB DIP Flash ROM
 - **Form Factor**
 - ITX form Factor:170x170 mm