


409.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel ATOM SoC !
- Tripple Display !
- 12-28V Input !
- 3,5" SBC !



- Powered by Intel® Atom X-series Processor(Formerly Amston Lake, TDP 9W)
- High-Performance Memory: 1 x DDR5 4800MHz SO-DIMM, up to 32GB
- Triple Display support: 2 x 4K HDMI, 1 x 4K USB Type-C DP, and 1 x LVDS/eDP output
- Dual 2.5GE LAN for high-speed networking
- Flexible storage and expansion option: 1 x SATA III, 1 x M.2 M-key, 1 x M.2 B-key, 1 x M.2 E-key
- Comprehensive I/O: 1 x USB 3.2 Gen 2, 1 x USB Type-C (ALT), 8 x USB 2.0, 6 x COM
- Advanced Power Protection: Supports RVP, OCP, and OVP
- Wide Power Input: DC-in 12~28V for greater power flexibility

MB FORM FACTOR

3.5"

CPU

Onboard Intel Atom® x7433RE Processor (Formerly Amston Lake, TDP 9W)

For additional compatible CPUs, please contact regional sales

CHIPSET

Intel® SoC

MEMORY

1 x DDR5 4800MHz, Single Channel SO-DIMM, up to 32GB

BIOS

UEFI

WAKE ON LAN

Yes

WATCHDOG TIMER

255 Levels

SECURITY

TPM2.0 (dTPM, Optional)

RTC BATTERY

Lithium Battery

DIMENSION (W X D)

148.0 (W) x 102.0 (D) mm (5.8" x 4.0")

OS SUPPORT

Windows® 11 (64bit)

Windows® 10 (64bit)

Linux

POWER	
POWER REQUIREMENT	DC-in 12~28V
POWER ON MODE	AT / ATX (Default) Mode
CONNECTOR	Internal 2-pin Header
DISPLAY	
GPU	Intel® UHD Graphics
LVDS	1 x 24-bit Dual Channel LVDS (Max. Resolution: 1920 x 1080 @60Hz / Co-Lay eDP)
Type-C DP	1 x Type-C DP1.4a (Max Resolution: 4096 x 2304@60Hz)
HDMI	1 x HDMI 2.0b (Max Resolution: 4096 x 2160@60Hz), 1 x HDMI 1.4 (Max Resolution: 4096 x 2160@30Hz)
MULTIPLE DISPLAY	Support 3 Displays
AUDIO	
CODEC	Realtek Audio Codec
COMBO	1 x Combo Audio Jack for Line-Out / Mic-In
AMPLIFIER	3W
LAN	
ETHERNET	2 x RJ45 for Intel® I226-V 2.5GbE
USB PORT	
	Internal Header for 4 x USB 2.0
USB	4 x USB 2.0
	1 x USB 3.2 Gen 2x1 Type-C (10Gbps) Support DP ALT Mode
	1 x USB 3.2 Gen 2x1 (10Gbps, Formerly USB 3.1 Gen 2)
SERIAL PORT	
COM	Internal Header for 1 x RS-232/422/485
	Internal Header for 5 x RS-232
INTERNAL I/O	
GPIO	8-Bit
SMBUS	Yes
FAN	1 x 4-pin Connector for System Fan (PWM Mode)
	HDD Active LED
	Power LED
FRONT PANEL	Power On/Off
	Reset
	1 x Chassis intrusion
ADDITIONAL	1 x AT/ATX Mode Selection
STORAGE	
SATA	1 x SATA III
	1 x SATA Power Connector
eMMC	Onboard 64GB eMMC 5.1 (optional)
EXPANSION	
	1 x B-Key 3042/3052 (USB 3.2/USB 2.0) for 4G/5G Module
M.2	1 x E-Key 2230 (USB 2.0/PCIe 3.0 x1)
	1 x M-Key 2280 (PCIe 3.0 x2) Support NVMe
SIM	1 x Nano SIM Card Slot
ENVIRONMENT & CERTIFICATION	
SHOCK	15G, 11ms duration
VIBRATION	1 Grms/ 5~ 500Hz/ Operation
OPERATING TEMPERATURE	-20°C ~ 60°C (-4°F ~ 140°F)
STORAGE TEMPERATURE	-20°C ~ 85°C (-4°F ~ 185°F)
OPERATING HUMIDITY	10 ~ 90% relative humidity, non-condensing
CERTIFICATION	CE/FCC Class A